

Canopy LED

Outdoor Luminaires



CE UK
CB

LED

IP66

IK10



Description

The Canopy LED is engineered for demanding outdoor environments, offering a robust, no-nonsense IP66-rated design. Mounted on a column, it provides full 360° illumination for comprehensive area coverage.

Application

- Security Lighting
- Road Ways
- Building Perimeters
- Car Parks

Body & Finish

Constructed from a robust die-cast housing and finished with a durable powder-coated surface, the fitting features a vandal-resistant polycarbonate lens. Each optical assembly is sealed with a silicone gasket, ensuring its IP66 protection rating.

Attachments

- Inbuilt PIR



Order Codes

| Wattage | Luminous Flux | lm/W | NW | Diameter | Height | Product Code |
|---------|---------------|----------|--------|----------|--------|----------------------|
| 25.0 W | 3417 lm | 137 lm/W | 8.9kg | 460 mm | 80 mm | SGL/LED/3417/CANOPY |
| 50.0 W | 6402 lm | 128 lm/W | 8.9kg | 460 mm | 80 mm | SGL/LED/6402/CANOPY |
| 75.0 W | 9750 lm | 130 lm/W | 9.9kg | 460 mm | 80 mm | SGL/LED/9750/CANOPY |
| 120.0 W | 13800 lm | 115 lm/W | 10.2kg | 460 mm | 80 mm | SGL/LED/13800/CANOPY |
| 150.0 W | 18000 lm | 120 lm/W | 10.2kg | 460 mm | 80 mm | SGL/LED/18000/CANOPY |

Additional lumen outputs are available due to mA ratings and codes may vary from those stated. Please contact us for further details.

Sizes

- Diameter: 460 mm (Head Only)
- Height: 80 mm (Head only)

Code Options

Contact us for more information

LED Boards

- PCB LED
- Colour Temperatures Available: 3000k/4000k/5000k/6000k/6500k
- All LED data and performance data is taken at an ambient temperature of +25°C

Control Gear

Tridonic/OSRAM

- Standard LED
- DALI Dimming LED
- Lightmesh Bluetooth

Main Attributes

- 50,000h L80 at 25°C
- Self Cooling
- MacAdam Step 3
- Colour Rendering Index >80
- 7 Year Guarantee*
- CE Marked

* Please refer to the Warranty for more information.

Photometrics

-